
## RSPian

Rope Suspended Platforms'




✓ SPARE PARTS

Model Type			ZLP 800
Rated Load			800 kg.
Lifting Speed			9 m/min
Max Lifting Height			100 Meter
Dimension of platform (L*W*H)			(2.5m x 2 +1m+1.5m) x 0.76m x 1.45m
Suspensi on mechanism	Front beam overhang		1.3 ~1.7 m
	Adjustable Height		1.15~1.75 m
Hoist	Model		LTD 8.0
	Lifting force		8 KN
	Motor	Power	1.8 KW
		Voltage	415 V, 50 HZ , 3 phase
		Rotation speed	1400 R/Min.
		Brake Torque	15.2 N-m
Safety lock	Туре		Tilt proof safety lock
	Locking cable angel		3-8 degree
	Allowable impulsive force		30 KN
Weight	Suspension platform including hoist, safety lock, electric control panel.		540 kg
	Suspension mechanism		400 kg
	Counterweight		1000 kg
	Whole machine weight without steel wire rope & power cable		1940 kg
Wire rope	Туре		4X31SW+FC-9.1
Platform type			Hot Dip Galvanized









## **RSPian**

## **RSPian Construction Equipment Solutions**

C-902, River Scape, Casa Rio,

Kalyan Shil Road, Thane - 421204, Maharashtra, INDIA

Mail: info@rspian.com, Web: www.rspian.com

CONTACT: +91 88280 55762

## Safety Devices List:

- . Safety Lock Device
- . Centrifugal Speed Limiter
- . Electromagnetic Brake with manual release
  - . Over Hoist / Top Limit Switch
    - . Anti-Tilting Cut off
- . Over current protection thro' Relay (OLR):
  - . Locking arrangement for upper counter weights
- . Hammer weight for wire rope locking
  - . Panel board Lock & key
- . Galvanized Wire rope with proper U Clamps
- . Anti-Sway Restriction (Optional)
- . Overload Cut-off using Load cell and display (Optional)
  - . Over Head Protection (Optional)
- . Cable Protection Device (Optional)